

MODULAR PROTECTION

MSL-24V-POWER - 12VDC / 24VAC POWER SURGE PROTECTOR

Features:

- Power protection module protects two power conductors (1 pair) using 2 #12 AWG screw terminals to ensure all conductive paths are protected.
- Solid-state protection provides the fastest response to transient voltages (1-5 nanoseconds) by quickly diverting damaging surges to ground.



ORDERING INFORMATION

ITW Linx Part Number	Description
MSL-24V-POWER	Protects two power conductors (1-pair). Using 2 #12 screw termination type . (MOQ 6)

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing *

For up-to-date warranty information, please visit our web site at www.itwlinx.com.

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

LED Indicators	N/A
Grounding Requirements See Technical Reference page 81-98 for additional grounding tips.
Recommended Grounding Impedance.....	<0.5 Ohm
Width.....	4.25"
Height.....	4.25"
Depth	1.5"
Weight.....	0.42 lbs
Warranty.....	1 Year from Manufacture

AC SURGE PROTECTION: N/A

SIGNAL LINE SURGE PROTECTION:

TELCO CIRCUIT PROTECTION N/A

COAX CIRCUIT PROTECTION N/A

DC POWER CIRCUIT PROTECTION

Signal Perfect Circuitry Yes

Auto-Resettable Yes

Fuse Rating 2.5A

Max. Clamping Level..... 30VAC

Response Time 1-5 Nanoseconds

Wires Protected 2-Wires, 1-Pair

Termination Type #12 Gauge Screw Terminals

For more technical information, refer to "TECHNICAL REFERENCE", page(81-98).

Signal Perfect™ - For more information, refer to page 81.



Secure Linx™