

MODULAR PROTECTION

MSL-CAT5-24V - LAN & POWER SECURITY CAMERA SURGE PROTECTOR



Features:

- Protects two power conductors (1 pair) using 2 #12 AWG screw terminals and provides 2 pair CAT5e protection without degrading the video signal performance.
- Utilizes 100% solid-state protection for fast reliable response to surge events and meets TIA568 and TIA758 for CAT5e performance.
- Solid-state protection provides the fastest response to transient voltages (1-5 nanoseconds) by quickly diverting damaging surges to ground.

ORDERING INFORMATION

ITW Linx Part Number	Description
MSL-CAT5-24V	Protects two power conductors (1-pair) and provides 2-pair CAT5e protection. 110 Punchdown and screw termination type. (MOQ 6)

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing *

For up-to-date warranty information, please visit our web site at www.itwlinx.com.

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

LED Indicators	N/A
Grounding Requirements	See Technical Reference page 81-98 for additional grounding tips.
Recommended Grounding Impedance.....	<0.5 Ohm
Width.....	4.25"
Height.....	4.25"
Depth.....	1.5"
Weight.....	0.42 lbs
Warranty.....	1 Year from Manufacture

AC SURGE PROTECTION:

SIGNAL LINE SURGE PROTECTION:

AC POWER CIRCUIT PROTECTION

Signal Perfect Circuitry / Auto-Resettable.....	Yes
Max. Clamping Level.....	30VAC
Response Time	1-5 Nanoseconds
Fuse Rating	2.5A
Wires Protected	2-wires, 1-pairs
Termination Type	#12 Gauge Screw Terminals

COAX CIRCUIT PROTECTION

LAN CIRCUIT PROTECTION

Signal Perfect Circuitry & Fuseless/Auto-Resettable.....	Yes
Performance Rating	Cat 5e
Clamping Level	16V
Response Time	1-5 Nanoseconds
Wires Protected	4-wires, 2-pairs
Termination Type	110 Punchdown

For more technical information, refer to "TECHNICAL REFERENCE", page(81-98).

Signal Perfect™ - For more information, refer to page 81.



SecureLinx™

